
EN 1092-1 · EN 1092-1:2018

EN 1092-1 PN25 DN350 Weld Neck

DN350 · Weld Neck · Dimensions mm · Weight kg

EN 1092-1 · DN350 · PN25 · Weld Neck Flange



Both views share one scale (1:8.8); schematic only

Unit: mm

Symbol	Item	Value
D	Outside diameter	555 mm
C	Flange thickness / blind thickness	38 mm
D2	Raised face diameter	450 mm
f	Raised face height	2 mm
K	Bolt circle diameter	490 mm
n	Number of bolt holes	16 pcs
d	Bolt hole diameter	33 mm
A	Hub diameter	398 mm
H	Hub length / overall length	100 mm
B	Welding-end diameter	355.6 mm
–	Approximate weight	48.8 kg

PRESSURE–TEMPERATURE RATINGS · PN25 · GROUP 3E0

RT °C	100 °C	150 °C	200 °C
25.0 bar	23.2 bar	22.0 bar	20.8 bar
250 °C	**300 °C**	**350 °C**	**400 °C**
19.0 bar	17.2 bar	16.0 bar	14.8 bar
450 °C			
8.2 bar			

Source: Tables G.2 to G.13 (pp. 113–124) — group 3E0 / P245GH (1.0352), vR ≤ 50 mm, all PN; Group 3E0.

MATERIAL AND NOTES

Base material: P250GH / S235JR (Europe, UK, Middle East, Africa, CIS projects)

Rating: EN 1092-1 uses PN (nominal pressure) ratings in bar: PN6, PN10, PN16, PN25 and PN40. PN16 means 16 bar nominal at ambient temperature for EN material group 1, derating with temperature per the EN 1092-1 tables. EN PN ratings are not equivalent to AS…

Tolerances / marking: Tolerances, material groups and marking: EN 1092-1:2018, including Annex G.

NOTES / SPECIAL REQUIREMENTS

Work order _____ Inspector _____ Date _____ Travels with the part; file after inspection

Source: EN 1092-1:2018; dimensions transcribed from EN 1092-1:2018, verified 2026-11-04. Sheet #794.

This sheet is a factual compilation of published standards tables and is not a substitute for the standard itself. Verify dimensions and ratings against the edition named in your purchase specification before quoting, manufacturing or inspecting a critical part.

Scan to open